

STELLAR ALUMINIUM BI-FOLD QUOTE FORM



Customer Details

Contact Email:

Contact Telephone:

VIEWED FROM OUTSIDE

Tick Box [s] For Required Design & Options

STANDARD DESIGNS WITH EXTERNAL ACCESS

3-3-0 **3-0-3**

4-3-1 **4-1-3**

5-5-0 **5-0-5**

6-5-1 **6-1-5**

6-3-3L **6-3-3R**

DENOTES AN EXTERNAL ACCESS DOOR

STANDARD DESIGNS NO EXTERNAL ACCESS

2-2-0 **2-0-2**

4-4-0 **4-0-4**

Configurations Explained eg. **4 - 3 - 1**

4 = Total Number of Leaves
3 = Leaves Folding Left
1 = Leaves Folding Right

Specification Note

Where required **ALL Magnets** to folding doors will be supplied loose for on site fitting. Before ordering please ensure you are familiar with the product and specification as no responsibility will be accepted by the company for any lack of knowledge in the event of the products suitability. Bi-Folds are not load bearing, under no circumstances should anything sit directly on top of the doors.

Warranty Note

We cannot guarantee any product installed within 100 metres of the coast, source of pollution or 2 metres away from a swimming pool against deterioration of profile or hardware. Any products fitted within 5000 metres of a hostile environment a recommended cleaning regime must be adhered to and recorded, please refer to our Bi-Fold aftercare guide.



OPENING Open **OUT**
 Open **IN**

SIZE Including Cills & Any Frame Extensions

WIDTH mm

HEIGHT mm

COLOUR STANDARD OPTIONS

WHITE
 Matt Finish

ANTHRACITE GREY
 Matt Finish

ANTH. GREY / WHITE
 Matt Finish

BLACK
 Matt Finish

BLACK / WHITE
 Matt Finish

BESPOKE COLOUR REQUEST

Outside _____

Inside _____

THRESHOLD

54mm Threshold

Face Drained as standard

Low Threshold (33.5mm)

[Room Divider] No weather rating

CILL

All cills are square cut to the width of the Bi-Fold

150mm

100mm

200mm

None

HANDLE COLOUR

External Access Door ONLY

GRAPHITE BLACK

GOLD CHROME

WHITE

FRAME EXTENDERS 18mm 36mm

TOP

Left Hand Side

Right Hand Side

TRICKLE VENTS [2 x 5000mm]

Routed For Fitting in 36mm Frame Extension Only

Trickle Vent Required

ENHANCED SECURITY

PAS 24

PAS 24 & SBD

UNGLAZED 28mm 36mm

GLAZED (28mm)

4mm Tough soft coat / 4mm Tough clear, Warm Edge

4mm Tough soft coat / 6.8mm Lami Clear, Warm Edge

GLAZED (36mm)

4mm Tough soft coat / 4mm Tough soft coat / 4mm Tough clear, Warm Edge

4mm Tough soft coat / 4mm Tough soft coat / 6.8mm Lami Clear, Warm Edge

OTHER State Glass Required Below
 I.E Integrated Blinds

Notes/Special Instructions

NOTE: Longer lead times and price premiums apply to BESPOKE colours

sales@eweplastics.co.uk

Phone: 01492 588679